

marrakech

DESIGN

Kaserntorget 6
411 18 Gothenburg
Sweden
Telephone: +4670 666 7520
Email: info@marrakechdesign.se

Our cement tiles are individually handmade (approximately 3 minutes/tile). The surface of our cement tiles is not glazed which means the tiles needs to be sealed during installation and then resealed once a year (depending on area where they are installed). Full product description and installation and maintenance recommendations can be found on our website.

Product Description:

Handmade cement tiles by Marrakech Design.

The raw materials are Portland cement, sand, marble powder, water and color pigments. Each cement tile is individually made and variations in thickness, size and color as well as imperfections like irregular edges and corners as well as pattern contours being partly blurred are inherent to the manufacturing process.

Grout & Adhesives:

Please install the tiles with products suitable for natural stone. We recommend light/medium grey colored grout and strongly advise against colored, black and white grout.

Underfloor heating:

Please install the tiles with at least 3-4 mm wide joints between the tiles. Floor heating can be turned on 10-12 weeks after installation.

Storage information:

Store in a cool, dry, frost-free environment

Outdoor installation:

Our cement tiles can be installed outdoors as long as the tiles are sealed. Please note that colors such as green, blue, red and yellow will bleach with time due to the UV. Please also install the tiles with frost proof grout and adhesives if the temperature will be -0.

Cleaning and maintenance:

One of the attributes of cement tiles is that they improve with age and wear and cleaning. The tiles should be regularly washed with mild soap and water. Never use bleach or acidic products to clean the tiles.